

Chemical composition

Components	percentage
Carbon:	0.9%~1.0%
Silicon:	14.25%~14.75%
Chromium:	4.3%~5.0%
Manganese	1.5% max
Molybdenum:	0.2% max
Iron:	Remainder

Specification


Anode Dimention (mm) :	Diameter:	76 mm
	Length:	1525 mm
	Head Diameter:	102 mm
	Surface Area:	0.38 m ²
Cable conection:		Lead Caulking

Cable(mm)	length: 3000 mm,	Size=1*16(mm2)
	Shiled:	Double Jacket XLPE/PVC

Encapsulation: Heat Shrinkable Cap

Backfill: Without Canister

Gross Weight: 49kg

Date:				Tavanazob Sanaati Kavir Manufacturer of Cathodic protection accessories Mahmoodabad industrial park, Qom-Tehran highway, Iran Tel: (+98-21)66159153 Fax: (+98-21)43851223 Email: Info@anode.ir Website: www.anode.ir		Client's Approval
	Description:	KAVIR				
Order number:				High Silicon Cast Iron Anode 3*60		
Drawn:		M. Sarabadan	Date:	05/06/2019	Project:	
Checked:		J.pourjam	Date:	05/07/2019	Approved by TAVANAZOB Co.	
Rev.	Approved:	A. Rahmani	Date:	05/07/2019	Standard: IPS-MTP-750	Sheet 1/1 A4